



























CHANNELS: UP TO



VIEW ON FULL HD TV



NIGHT VISION: UP TO 20 METRES



24/7 SURVEILLANCE



USB BACKUP



PUSH NOTIFICATIONS & EMAIL ALERTS

FULL HD DVR UNIT

000000000

NPUT PANEL

00000

VGA Out

2. Network (Ethernet)

1.

3. GND



RECORD & WATCH FOOTAGE VIA SMARTPHONE OR TABLET



GDVR SERIES SPECIFICATIONS

Embedded processor

Embedded LINUX OS

SYSTEM

Main Processor **Operating System**

VIDEO

Analog HDTVI

GDVR 4T40 4 channel, BNC GDVR 8T40 8 channel, BNC GDVR 8T80 8 channel, BNC

1080P/720P HDTVI Camera

AUDIO

Input

Input Output 4 channel, RCA 1 channel, RCA

DISPLAY

Interface Resolution

Standard

Display Split

Privacy Masking

OSD (On Screen Display)

1 HDMI, 1 VGA 1920×1080, 1280×1024, 1280×720, 1024×768, 800x600 **GDVR 4T40** 1/4 GDVR 8T40 1/4/8/9

GDVR 8T80 1/4/8/9 4 rectangular zones (each cameral

Camera title, Time, Video loss, Motion detection, Recording

RECORDING

Video/Audio Compression H.264/G.711A

Main Stream: 1080P, 720P, Record Rate

960H (up to 15fps) Extra Stream: CIF (up to

Bit Rate 256~2048Kb/s

Record Mode Manual, Schedule, Motion Detection, Sensor

Record Interval N/A

VIDEO DETECTION & ALARM

Motion Detection Video Detection

PLAYBACK & BACKUP

1/4 Svnc Plavback

Search Mode

Time/Date, Motion Detection, Sensor

Playback Functions

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection

Backup Mode

NETWORK

Ethernet Network Functions

Max. User Access Smart Phone

STORAGE

Internal HDD

1 SATA port GDVR 4T40 1TB Included **GDVR 8T40** 1TB Included

AUXILIARY INTERFACE

USB Interface RS485

GENERAL

Power Supply Working Environment DC12V/2A -20°C~+50°C/ 10%~90%RH

1/2.7" CMOS

3 USB2.0 port

RJ-45 port (10/100M) HTTP, IPv4, TCP UPNP,

DHCP, PPP₀E, DDNS,

iPhone®, iPad®, Android

GDVR 8T80 2TB Included

1 port, For PTZ Control

FTP, P2P

10 users

CAMERA

Image Sensor Effective Pixels **Electronic Shutter** Video Frame Rate Min. Illumination

Video Output

1984×1105 2 Megapixel 1/50s~1/10,000s up to 25fps@1080P 0.1Lux with IR Off, 0 Lux IR On

1-channel BNC High definition video output

20m

CAMERA FEATURES

Max. IR LEDs Length Colour

LENS Focal Length Angle of View Mount Type

AUDIO

Microphone Audio Range Wall/Ceiling plastic

N/A

GENERAL

Power Supply Power Consumption Working Environment

Transmission Distance

Ingress Protection Material

3.6mm fixed lens

Day: Colour / Night: B/W

N/A

DC12V

Max 6W

-20°C~+50°C. 10% / Less than 90%RH Over 500m via RG59 coaxial cable

IP66* Plastic

RS-485 10. Video/Audio Out **Communication Port** 11. Camera Input (Only 4 ports for USB Mouse Model: GDVR 4T40)

7. USB2.0

8. Audio Input

9. HDMI Out

USB Device

FOLLOW US ON





DISCOVER