

Uniden®

GUARDIAN™



PROFESSIONAL

FULL HD TECHNOLOGY
NVR SECURITY SYSTEMS

GNVR167XX & GNVR87XX SERIES

SUPPORTS UP TO

4MP

IP CAMERAS



UP TO 16
CHANNELS



VIEW ON TV



24/7
SURVEILLANCE



USB BACKUP




PUSH
NOTIFICATIONS &
EMAIL ALERTS



RECORD & WATCH
FOOTAGE VIA
SMARTPHONE
OR TABLET

IN-BUILT INTELLIGENCE



TRIPWIRE

System generates an alarm once any object crosses the tripwire in the specified direction.



INTRUSION

Security System generates an alarm once any object enters or exits the zone in the specified direction.



OBJECT DETECTION

Security System generates an alarm when an object goes missing/abandoned in a specified zone.



SCENE CHANGE

When the detected scene changes, the Security system generates an alarm. e.g. If a person deliberately moves the angle of the camera.

FULL HD SECURITY SYSTEM IN THE PALM OF YOUR HAND


Enjoy the comfort of having the control in the palm of your hand – push notifications with instant alerts from anywhere in the world via our FREE app for smartphones & tablets.

REMOTE VIEWING
Anytime. Anywhere
in the World.




FREE APP
GUARDIAN LIVE PRO
FOR SMARTPHONES & TABLETS





GNVR 8740


This system comes with 4 IP outdoor cameras [GNC710]



GNRV 16700 Series

This is a standalone system without cameras. See OPTIONAL compatible camera list below.

INPUT PANELS



- GNRV167xx**
1. Power
 2. Camera Input
 3. Network (Ethernet)
 4. VGA
 5. Mic Out/In
 6. HDMI
 7. USB 3.0
 8. RS485/Alarm Port
 9. RS232
 10. eSATA

- GNVR87xx**
1. Power
 2. Camera Input
 3. Network (Ethernet)
 4. VGA
 5. Mic Out/In
 6. HDMI
 7. USB Mouse
 8. RS485

INSIDE THE BOX

- GNRV16700**
- NVR Unit (x1)
 - HDMI Cable (x1)
 - Ethernet Cable (x1)
 - Mouse (x1)
 - AC Power Adaptor (x1)
 - Mounting Kit (x1)
 - Security Stickers (x1)

- GNVR8740**
- NVR Unit (x1)
 - GNC710 IP Camera (x4)
 - HDMI Cable (x1)
 - Ethernet Cable (x1)
 - Mouse (x1)
 - AC Power Adaptor (x1)
 - 30m Ethernet Cable for IP Camera (x4)
 - Mounting Kit (x1)
 - Security Stickers (x1)

OPTIONAL CAMERAS

GNC701
OPTIONAL DOME CAMERA



GNC710
OPTIONAL OUTDOOR CAMERA



GNC710 (x4)
OPTIONAL OUTDOOR 4 CAMERA PACK



GNC701ML
OPTIONAL DOME MOTORISED CAMERA



GNC710ML
OPTIONAL OUTDOOR MOTORISED CAMERA





SYSTEM SPECIFICATIONS

SYSTEM

Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX

VIDEO

IP Camera Input (GNVR8740)	8 channel
IP Camera Input (GNVR16700)	16 channel
Audio Input	1 Channel
Audio Output	1 Channel

DISPLAY

Interface	1 HDMI, 1 VGA
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Display Split (GNVR8740)	1/4/8/9
Display Split (GNVR16700)	1/4/8/9/16
Privacy Masking	4 rectangular zones (each camera)
On Screen Display	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

RECORDING

Video Compression	H.264/MJPEG
Supported Resolution	2560 x1440 (4MP) 2048x1536 (3MP), 1920x1080 (FullHD), 1280x720 (HD), 704x576 (D1)

Bit Rate	48-8192Kb/s
Record Mode	Manual, Schedule, Motion Detection
Record Interval	1-120 min (default: 60 min)

VIDEO DETECTION & ALARM

Video Detection	Motion Detection, Video Loss & Camera Blank
-----------------	---

PLAYBACK & BACKUP

Sync Playback (GNVR8740)	1/4/9
Sync Playback (GNVR16700)	1/4/9/16
Search Mode	Time/Date, Motion Detection & Exact search (accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Backup Mode	USB Device

NETWORK

Ethernet (GNVR8740)	1 RJ-45 port (10/100M)
Ethernet (GNVR16700)	1 RJ-45 port (10/100M/1000M)
PoE (GNVR8740)	8 ports
PoE (GNVR16700)	16 ports
Network Functions	Supports IPv4/IPv6, TCP/IP, DHCP, P2P
Smart Phone	iPhone, iPad, Android

STORAGE

Internal HDD (GNVR8740)	2TB included
Internal HDD (GNVR16700)	2TB included, Supports Upto 4 HDD

AUXILIARY INTERFACE

USB Interface (GNVR8740)	2 USB2.0 port
USB Interface (GNVR16700)	1 USB2.0 port (front), 1 USB3.0 (rear)

GENERAL

Power Supply (GNVR8740)	DC48V/2A
Power Supply (GNVR16700)	AC240V
Working Environment	-10°C ~+55°C



For complete range details, scan QR Code or visit Uniden at:
uniden.com.au or call **1300 366 895** today.

FOLLOW US



Minimum Network Bandwidth Requirements: For optimal performance of the smartphone app we advise a minimum network bandwidth of 4Mbps for Full HD (1080P) live stream, 2Mbps for HD (720P) live stream and 0.8Mbps for 352P live stream. If these bandwidth requirements are not met the live stream may not connect and will not be viewable on your smartphone.

*IP66 Weatherproof is defined as no ingress of dust; complete protection against contact (dust tight) and Water projected in powerful jets (12.5 mm nozzle) against the enclosure from any direction shall have no harmful effects. Some jurisdictions and authorities may regulate the use of surveillance products. It is the buyers responsibility to ensure they comply with the appropriate regulations when using this product. Specifications Subject to Change Without Notice. See Uniden Website for any changes: www.uniden.com.au Unit must only be used in country of purchase. All brand names are registered trademarks of their respective owners. Uniden Guardian® is a trademark of Uniden Australia Pty Ltd. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play, and the Google Play logo are trademarks of Google Inc. All diagrams, product photography and front cover photograph of hand and smartphone are for illustration purposes only. Some products may vary at the time of production. Smartphone not included.