



















CHANNELS: UP TO



SUPPORTS UP TO 5MP IP CAMERA



NIGHT VISION: UP TO 30 METRES



24/7 SURVEILLANCE



USB BACKUP



PUSH NOTIFICATIONS & EMAIL ALERTS



RECORD & WATCH FOOTAGE VIA SMARTPHONE OR TABLET



FULL HD NVR UNIT **INPUT PANELS**



GNVR 49xx SERIES SPECIFICATIONS

Main Processor
Operating System

IP Camera Input

Display Split Privacy Masking On Screen Display

Bit Rate Record Mode

Wireless Network Max. User Access Smart Phone

Dual-core embedded processor Embedded LINUX

Up To 4 Channels

1 HDMI, 1 VGA 1920×1080, 1280×1024, 1280×720, 1024×768

4 rectangular zones (each camera) Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Video/Audio Compression H.264/MJPEG

2560 x 1920 (5MP), 2048x1536 (3MP), 1920x1080 (FullHD), 1280x720 (HD), 704x576 (D1) 48~8192Kb/s Manual, Schedule, Motion Detection

VIDEO DETECTION & ALARM Video Detection

Sync Playback Search Mode

Motion Detection, Video Loss & Camera Blank

Play, Pause, Stop, Rewind, Fast play, Slow play USB Device

1 RJ-45 port (10/100M) IPv4/IPv6, TCP/IP, P2P Built-in Wi-Fi (AP) 128 users iPhone®, iPad®, Android

Power Supply Working Environment

APP CAM 35 CAMERA

Image Sensor

Video Frame Rate

CAMERA FEATURES Max. IR LEDs Length Day/Night Micro SD

Mount Type Pan/Tilt Range

GENERAL Power Supply Power Consumption

1 SATA port, 1TB included

2 USB2.0 port

DC12V/2A -10°C ~+55°C

1/3" progressive scan CMOS 2304 x1536 3 MP 1/3s~1/100000s up to 20fps@3MP / up to 25 fps@1080P/720P 0.1Lux@F2.0(color), 0Lux with IR on

Color / B/W Up to 64GB

Board-in Type

N/A N/A

Metal

DC 12V Max 5.5 W -10°C~+45°C 50m (line of sight) via Wi-Fi IP66*

FOLLOW US ON









